HP Everyday Adhesive Matte Polypropylene, 3-in Core




This product is only compatible with HP Latex Printers



The HP large format printing system—the complete solution

HP Designjet, HP Latex, and HP Scitex Printers, Original HP inks and printheads, and Original HP printing materials are designed to work together as a system to provide reliable, consistent results with every print.



High-quality prints for your day-to-day production

Produce eye-catching displays

See outstanding image quality. Work with the wide color gamut and smooth transitions delivered by this matte polypropylene material and produce quality prints from line drawings to photo-quality POP displays.

Gain efficiency

Help keep your production process moving smoothly. This easy-to-use film features a permanent self adhesive for secure, reliable mounting. Prints can be easily removed.¹

Make the versatility of this material work for you

ICC profiles help you get the right color, right away. Take advantage of compatibility with Original HP Latex, low-solvent, and UV-curable inks on this versatile, easy-to-use printing material.

Target customers	Applications	Benefits	
Print service providers	POP and retail displays	Outstanding image quality for day-to-day production	
Retail store in-house printing	Trade show and event displays	A permanent self-adhesive for secure, reliable mounting	
Event designers	Temporary exhibitions	Easy to use and remove, with a limited HP warranty ¹	
Advertising agencies	Architecture competitions		
Geographic Information Systems (GIS)			
Government (printing self- adhesive maps)	-		

HP Everyday Adhesive Matte Polypropylene can be easily removed. Residual adhesive can be easily wiped clean. Some warranty limitations apply, see the Limited Warranty statement at <u>globalBMG.com/</u> hp/mediawarranties.

Technical specifications



HP Everyday Adhesive Matte Polypropylene, 3-in Core

For the latest ICC profiles/paper presets, please visit globalBMG.com/hp/paperpresets.

Weight (without liner)	120 g/m² per ISO	536 Test Method			
Weight (with liner)	168 g/m² per ISO 536 Test Method				
Thickness (without liner)	180 microns/7.1 mil per ISO 534 Test Method				
Thickness (with liner)	215 microns/8.5 mil per ISO 534 Test Method				
Opacity (with liner)	Greater than 96% per TAPPI T-425 and ISO 2471 Test Methods				
Brightness (with liner)	101% per ISO 2470 Test Method				
Whiteness (without liner)	Greater than 120 per ISO 11476 Test Method				
Whiteness (with liner)	150 per ISO 11475 Test Method				
Finish	Matte				
Operating temperature	15 to 35° C / 59 to 95° F				
Operating humidity	20 to 80% RH				
Dry time	Less than 2 minutes (at 23° C, 50% RH)				
Lamination	Yes				
Shelf life	2 years, unopened in original packaging				
Storage temperature	15 to 35° C / 59 to 95° F				
Storage humidity	15 to 30% RH				
Country of origin	Product of China				
Ordering information	Product numbers	Roll sizes	UPC codes	Region	
	D9R24A	914 mm x 30,5 m (36 in x 100 ft)	848412009798	North America, Europe, Asia	
	D9R25A	1067 mm x 30,5 m (42 in x 100 ft)	848412009804	North America, Europe, Asia	
	D9R26A	1270 mm x 30,5 m (50 in x 100 ft)	848412009811	North America, Europe, Asia	
	D9R27A	1524 mm x 30,5 m (60 in x 100 ft)	848412009828	North America, Europe, Asia	
Warranty	HP offers a range of self-adhesive materials with warranties that guarantee these products to be free of mater or coating flaws and defects that affect the final use of the print and meet HP published specifications. For warranty statement please see globalBMG.com/hp/mediawarranties.				

For information about HP Sign and Display Printing Materials for HP Latex and UV printers, please visit globalBMG.com/hp/signagemedia

For information about HP Graphics and Technical Printing Materials for HP Designjet T & Z series printers, please visit hp.com/go/LFPrintingMaterials

